





















# FalCo Solution Access Control & Temperature Screening Terminal & Kiosk

FalCo Solution Co.,Ltd. 47/319, 5th floor, KaiTak Building, Popular Road, Ban Mai Subdistrict, Pak Kret District Nonthaburi Province, 11120 Thailand Tax ID: 0135558013787

Item No.	Price list (Baht) Exc.VAT	Picture	Main Function	Specifications
<b>Barbary IoT Product Solution</b>				
<b>BBR-GW-BLE5</b>	<b>13,225.00</b>		<b>Barbary Beacon IoT Gateway BLE5.0 with WIFI (BRB-GW-BLE5)</b> It's a faster and safer gateway with powerful Bluetooth® LE & Wi-Fi CPU and WPA 2.0 enterprise encryption for data security and transmission, G1 collects data from Bluetooth® LE Beacon, sensor and other IoT devices, and then sends it to the cloud over Wi-Fi / Ethernet. It's a great option for all industry applications.	Super Speedy WiFi CPU & Bluetooth 5.0 Chipset Bluetooth RF Power Accuracy Scanning & concurrently process 300 Bluetooth® LE packets per second Range up to 300 meters in open space Wireless IEEE 802.11b/g/n (single stream) Frequency band 2.400 – 2.484 GHz Range up to 90 meters( in open space) Size 150x150x36mm Power supply (Vcc) DC 5.0 (+/- 5%) Max. 5.5 Volts Support AWS/Azure/Google IoT Cloud Platforms Warranty 1Year
<b>BBR-UMG01</b>	<b>4,409.00</b>		<b>USB Mini Gateway (BBR-UMG01)</b> BBR-UMG01, powered by USB, is a plug-and-play Bluetooth® LE gateway used for the detection and data collection of Bluetooth devices. Users can monitor and locate Bluetooth devices on the cloud platform to manage personnel, facilities, assets, and environments remotely. Number of Received Broadcast Packets 70 packets / second Scan Coverage 70 meters of covered radius	Bluetooth® LE 5.0 Plug and play & quick setup Small and swift & flexible installation High throughput & data filterable Strong compatibility & easy integration Secure data transmission Number of Received Broadcast Packets 70 packets / second Scan Coverage 70 meters of covered radius Material ABS Weight 9g Work Temperature -20°C ~ 55°C USB powered Dimension 50 * 24 * 10.5 mm
<b>BBR-ND-ULR (&gt;5 Node)</b>	<b>3,623.00</b>		<b>Ultra-Long Range Beacon (Lithium Battery, Screw Bracket) (BBR-ND-ULR)</b> Bluetooth® LE 5.0 & nRF52 Series IP67 Waterproof & Dustproof Compatible with 1 Mbps / 125 Kbps External Operation Button Longer Range. Bigger Battery.	Dimensions (L*W*H) 72*72*23 mm Operating Temperature -20 °C~65 °C / -18~50 °C (Depend on the battery) Weight 129 g / 153.4 g (Depend on the battery) Material Plastic PC+ABS Chip nRF52833 / nRF52840 (Optional) Battery Lithium / Alkaline Battery; 10800mAh / 5800mAh Broadcasting Range Up to 1,968 ft (600 m) IP Certified IP67 Waterproof & Dustproof Sensors Accelerometer Optional Installation Screw bracket (Optional) Warranty 1Year
<b>BBR-LB (&gt;5 Node)</b>	<b>2,473.00</b>		<b>Location Beacon (BBR-LB)</b> Battery Life 6.5 years (default setting) Protection IP67 Sensor Accelerometer supported Broadcast Range 150 m / 492 ft (open area) Working Temperature Range 20 °C ~ 60°C	Material ABS+PC Weight 40.9 g Battery Capacity 200 mAh Battery Life 6.5 years (default setting) Protection IP67 Sensor Accelerometer supported LED Blue & red light OTA via Configuration App BeaconSET+ Chip nRF52 series Bluetooth Protocol Bluetooth® LE 5.0 Broadcast Range 150 m / 492 ft (open area) Working Temperature Range 20 °C ~ 60°C Warranty 1Year
<b>BBR-PLB (&gt;5 Node)</b>	<b>2,473.00</b>		<b>Proximity Location Beacon (BBR-PLB)</b> Working temperature 20 ~ 60°C Battery 1 lithium battery; 4000 mAh; 10 years (under default configuration) Broadcasting Range Up to 492 ft (150 m)	Dimension 71.98 * 30.5 mm (without the bracket) Ø 75.04 * 34 mm (with the bracket. *available for additional purchase) Color White Working temperature 20 ~ 60°C Weight 55 g (without the bracket) Material PC Bluetooth version Bluetooth® LE 5.0 Chip Model nRF52 series Battery 1 lithium battery; 4000 mAh; 10 years (under default configuration) Broadcasting Range Up to 492 ft (150 m) Warranty 1Year
<b>BBR-THS (&gt;10 Node)</b>	<b>5,118.00</b>		<b>Temperature Humidity Sensor (BBR-THS)</b> Bluetooth® LE 5.0 & nRF52 Series 3 years battery life IP66 waterproof Operating temperature: -40 ~ 60°C Long peripheral probe High-accuracy sensor included	Dimension 70.6x38x17.8mm Weight 37.5g Materials ABS Mesh(Optional) Tamper-proof OTA(Optional) Waterproof IP66 Broadcasting range 100m Battery Alkaline battery, 1000mAh, 3 years Built-in sensor Temperature & Humidity Warranty 1Year
<b>BBR-THSS (&gt;10 Node)</b>	<b>5,923.00</b>		<b>Temperature Humidity Sensor Display Screen (BBR-THSS)</b> E-paper display Bluetooth® LE 5.0 & nRF52 Series OTA available Up to 24 months battery life Accelerometer available (Optional) IP66 Waterproof & dustproof 3 years battery life	Dimension 81x45x22mm (short probe); 109.5x45x22mm (long probe) Operating temperature range -25~60°C Weight 60.5g(Battery included) Materials PC Waterproof & Dustproof IP66 Battery Lithium battery, 1200mAh, 2years Warranty 1Year
<b>BBR-WBBC (&gt;10 Node)</b>	<b>1,943.00</b>		<b>Wearable Beacon (BBR-WBBC)</b> Smart Wearable Bluetooth® LE 5.0 & nRF52 Series The max. 50 meters advertising distance Up to 8 month battery lifetime Battery CR Series	Dimension 42.3x31x11.6mm Weight 18g (Battery & Strip included) Materials ABS Temperature -20 to 60C Battery CR series coin battery , 230mAh. Battery life 8 month Broadcasting range 50m Bluetooth protocol BLE5.0 Warranty 1Year
<b>BBR-CDBC (&gt;10 Node)</b>	<b>2,473.00</b>		<b>Card Beacon (BBR-CDBC)</b> Panic button Bluetooth® LE 5.0 The max. 50 meters advertising distance Battery life 2Year Waterproof IP65 Accelerometer Included RFID (NFC) option	Dimension 85.5x54.4.5mm Weight 18.5g/15.5g Materials ABS+PC Waterproof IP65 Temperature -20 to 60C Battery Li-MnO2 Battery 800/500mAh (Optional) Battery life 2/1.5 Year Broadcasting range 100m Bluetooth protocol BLE5.0 Accelerometer Optional Warranty 1Year
















# FalCo Solution Access Control & Temperature Screening Terminal & Kiosk

FalCo Solution Co.,Ltd. 47/319, 5th floor, KaiTak Building, Popular Road, Ban Mai Subdistrict, Pak Kret District Nonthaburi Province, 11120 Thailand Tax ID: 0135558013787

Item No.	Price list (Baht) Exc.VAT	Picture	Main Function	Specifications
<b>BBR-CBRB (&gt;10 Node)</b>	<b>2,653.00</b>		<b>Card Bluetooth Rechargeable Badg (BBR-CBRB)</b> Resistant level IP67 Battery 1 rechargeable battery, 270 mAh Battery life Up to 3 months Charging time About 2 hour Sensor Accelerometer Button External button Vibration motor Yes	Material ABS + PC Broadcasting range 100m Color White Size (L * W * H) 86 * 55 * 6 mm Weight 20 g Resistant level IP67 Battery 1 rechargeable battery, 270 mAh Battery life Up to 3 months Charging time About 2 h Sensor Accelerometer Button External button Vibration motor Yes RFID LF/HF/UHF (optional) OTA supported Bluetooth version Bluetooth® LE 5.0 Warranty 1Year
<b>BBR-LTS (&gt;10 Node)</b>	<b>1,943.00</b>		<b>Keychain Beacon (BBR-KCBC)</b> Bluetooth® LE 5.0 Protective housing With key-chain hole Push button The max. 70 meters advertising distance	Dimension 35x8mm Weight 7.0g (Battery Included) Materials PC+Aluminium Alloy Waterproof IP65 Battery CR series button battery, 160mAh Transmission range 70m Warranty 1Year
<b>BBR-LTS (&gt;10 Node)</b>	<b>1,943.00</b>		<b>Light Sensor (BBR-LTS)</b> Bluetooth® LE 5.0 & nRF52 Series IP65 waterproof Light sensor inside The max. 50 meters advertising distance Up to 5 years battery lifetime Ultrasonic assembling technology	Dimension 52.6x23.7x5.3mm Weight 7.0g Materials ABS Waterproof IP65 Battery CR series button battery, 220mAh Built-in sensor Light sensor Transmission range 50m Warranty 1Year
<b>BBR-AST (&gt;10 Node)</b>	<b>1,668.00</b>		<b>Asset Tag (BBR-AST)</b> Bluetooth® LE 5.0 & nRF52 Series Advertise iBeacon & Eddystone & Sensor data Low power consumption 3-axis accelerometer Replaceable battery The max. 60 meters advertising distance	Dimension 36.5x23.7x5mm Weight 6.5g Materials ABS Battery 1pc CR coin battery, 230mAh, 200days Built-in sensor accelerometer Advertising range 60m Warranty 1Year
<b>BBR-DBC (&gt;10 Node)</b>	<b>2,473.00</b>		<b>Dear Beacon (BBR-DBC)</b> Bluetooth® LE 5.0 IP67 Waterproof & Dustproof Replaceable coin battery The max. 100 meters advertising distance Internal ON/OFF push button Accelerometer sensor option	Dimensions (L*W*H) 57.8x40.6x17.5mm Weight 25g (Battery included) Waterproof IP67 Material ABS Battery CR series, 1000mAh, 18 months Transmission range 100m. Warranty 1Year
<b>BBR-VBS (&gt;10 Node)</b>	<b>2,473.00</b>		<b>Vibration Sensor (BBR-VBS)</b> 5 configurable sensitive levels 3 customized monitoring periods Rotatable buckle design Demo cloud platform & API available Customization service	Dimensions (L*W*H) 36.6*36.6*9.7 mm Operating Temperature -20~60°C Net Weight 11.1g Material ABS Chip nRF52 series Battery 1 pc CR series battery Sensors Vibration Sensor Warranty 1Year
<b>BBR-PIS (&gt;10 Node)</b>	<b>5,118.00</b>		<b>Passive Infrared Sensor (BBR-PIS)</b> nRF52 Series & Bluetooth® LE 5.0 3 Customized Monitoring Periods 2 Years Lifetime & Replaceable Battery Alarm Time Configurable PIR, ACC, T&H Sensors Included Angles Adjustable with Rotating Bracket	Dimensions (L*W*H) 90*52*38mm Operating Temperature -15~50°C Net Weight 96g+10g (Battery & Accessories included) Material ABS Chip nRF52 series Battery 2 pcs AA batteries, 2900mAh capacity in total Sensors PIR, Accelerometer, Temperature & Humidity Sensors (Included) Warranty 1Year
<b>BBR-DSS (&gt;10 Node)</b>	<b>2,473.00</b>		<b>Door Sensor (BBR-DSS)</b> Bluetooth® LE 5.0 & nRF52 Series Data Received by the Gateway Tamp Alarm OTA Available 2000 Pieces of Data Local Storage Replaceable Battery	Dimension 55x26.2x13mm (main body), 38.5x12.5x11mm (magnet) Weight 26.6g (with battery) Materials ABS Battery 230mAh, 13months (by default) Operating temperature -20~60°C Broadcasting range 100m Warranty 1Year
<b>BBR-PLBC (&gt;10 Node)</b>	<b>2,128.00</b>		<b>Pallet Beacon (BBR-PLBC)</b> Slim, lightweight design Up to 40 months service life Accidental shutdown prevention IK08 shockproof IP65 waterproof & dustproof 100m broadcasting range	Materials ABS Protection IP65, IK08 Dimensions (L*W*H) 116.1*25.2*9.2mm Net Weight 19g Battery 1200mAh capacity Chip Model nRF52 series Bluetooth Standard Bluetooth® LE 5.0 Warranty 1Year
<b>BBR-PRBC (&gt;10 Node)</b>	<b>3,048.00</b>		<b>Plus Robust Beacon (BBR-PRBC)</b> Bluetooth® LE 5.0 & nRF52 Series Magnetic switch Sensors compatible IP68 Dust & Waterproof IK09 Shockproof	Size 69.6x47.6x24mm Weight 52.2g Materials PC Bluetooth BLE 5.0, nRF52 Battery Lithium battery Battery Life Up to 44 months (Ref.) Battery Capacity 1200mAh Operating Temperature -40°C to 85°C Warranty 1Year
<b>BBR-RSBC (&gt;10 Node)</b>	<b>2,473.00</b>		<b>Road Stud Beacon (BBR-RSBC)</b> Bluetooth® LE 5.0 & nRF52 Series Advertise iBeacon & Eddystone simultaneously Up to 3 years battery lifetime IP68 waterproof & dustproof IK08 shockproof The max. 80 meters advertising distance	Size 100x100x25mm Weight 140.0g (Battery included) Materials ASA Waterproof & Shockproof IP68/IK08 Battery 1pc Lithium battery, 2700mAh, 3 years Broadcasting range 30m (Open area) / 80m (Hang in the air) Warranty 1Year

















# FalCo Solution Access Control & Temperature Screening Terminal & Kiosk

FalCo Solution Co.,Ltd. 47/319, 5th floor, KaiTak Building, Popular Road, Ban Mai Subdistrict, Pak Kret District Nonthaburi Province, 11120 Thailand Tax ID: 0135558013787

Item No.	Price list (Baht) Exc.VAT	Picture	Main Function	Specifications
<b>BBR-ILBC (&gt;10 Node)</b>	<b>2,473.00</b>		<b>Indoor Location Beacon (BBR-ILBC)</b> Bluetooth® LE 5.0 & nRF52 Series Up to 6 years lifetime Replaceable battery Up to 200m broadcasting range	Size 73.5×44.8×24.2mm Weight 56.0g(Battery included) Materials ABS+Silicone Battery AA battery 2900mAh capacity / Lithium battery 5400mAh capacity Battery Lifetime 3 / 6 years Warranty 1Year
<b>BBR-MNBC (&gt;10 Node)</b>	<b>1,035.00</b>		<b>Mini Beacon Tag (BBR-MNBC)</b> Programmed standard iBeacon firmware Up to 3 months battery lifetime, replaceable The max. 50 meters advertising distance Portable design User friendly enclosure Labeling available	Dimension 42.1×23.8×3.5mm Weight 4.5g(Battery included) Materials ABS Battery CR series button battery, 90mAh, 3 months Transmission range 50m Warranty 1Year
<b>BBR-LTBC (&gt;10 Node)</b>	<b>2,473.00</b>		<b>Light Beacon (BBR-LTBC)</b> IP65 waterproof Light sensor Included The max. 50 meters advertising distance Small size, ultrasonic assembling technology	Dimension 42.5×23.5×5.3mm Weight 6.5g Materials ABS Bluetooth protocol BLE 5.0 Chip nRF52 series Waterproof IP65 Battery 1pcs CR series button battery, 230mAh, 1-3 years (Depends on use conditons) Built-in sensor Light sensor Transmission range 50m Warranty 1Year
<b>BBR-UTBC (&gt;10 Node)</b>	<b>1,438.00</b>		<b>Ultra-thin Tag (BBR-UTBC)</b> Ultra-thin Battery replaceable The max. 50 meters advertising distance Battery CR series button battery, 90mAh Battery Life 3 months Compact design	Dimension 36.5×23.5×3.5mm Weight 4.5g (Battery included) Materials ABS Bluetooth protocol Bluetooth® LE 5.0 Battery CR series button battery, 90mAh Battery Life 3 months Transmission range 50m Warranty 1Year
<b>BBR-CTBC (&gt;10 Node)</b>	<b>1,438.00</b>		<b>Coin Tag (BBR-CTBC)</b> Bluetooth® LE 5.0 & nRF52 Series Battery replaceable The max. 50 meters advertising distance Battery CR series button battery, 90mAh, 3 months Mini size OTA available Cost-effective	Dimension Ø26x5mm Weight 4.0g(Battery included) Materials ABS Bluetooth protocol Bluetooth® LE 5.0 Chip nRF51 series Battery CR series button battery, 90mAh, 3 months Transmission range 50m Warranty 1Year
<b>BBR-PSBC (&gt;10 Node)</b>	<b>2,473.00</b>		<b>Plus Beacon (BBR-PSBC)</b> Waterproof & Dustproof Replaceable coin battery Advertising iBeacon & Eddystone High-accuracy accelerometer(optional) Max. 100 meters advertising distance Internal power push button Battery 1 x CR series, 1000mAh	Dimension Ø39×15.5mm Weight 20.2g (Battery included) Materials ABS Bluetooth protocol Bluetooth® LE 5.0 Waterproof IP67 Battery 1 x CR series, 1000mAh Advertising range 100m Warranty 1Year
<b>BBR-LCBC (&gt;10 Node)</b>	<b>2,473.00</b>		<b>Location Beacon (BBR-LCBC)</b> Bluetooth® LE 5.0 & nRF52 Series Advertise iBeacon & Eddystone simultaneously Replaceable battery, 2400mAh The max. 120 meters advertising distance Internal power ON/OFF push button Operation temperature -30 to 60°C	Size Ø50×20.5mm Weight 39.0g(Battery included) Materials PC Bluetooth protocol Bluetooth® LE 5.0 Chip nRF52 series Battery Lithium battery, 2400mAh Broadcasting range 120m Warranty 1Year
<b>BBR-RBBC (&gt;10 Node)</b>	<b>2,473.00</b>		<b>Robust Beacon (BBR-RBBC)</b> Bluetooth® LE 5.0 & nRF52 Series Advertise iBeacon & Eddystone simultaneously IP66 Waterproof & Dustproof Up to 5 years battery lifetime Replaceable AA battery The max. 200 meters advertising distance	Size 73.8×47×24.5mm Weight 80g (Battery included) Materials ABS Bluetooth protocol Bluetooth® LE 5.0 Waterproof & Dustproof IP67 Battery AA battery / Lithium battery(Optional), (Battery excluded for shipping) Broadcasting range 200m Warranty 1Year
<b>BBR-NUC (&gt;5 Node)</b>	<b>29,325.00</b>		<b>BBR NUC PoE Controller (BBR-NUC)</b> Gigabit Ethernet RJ45 connector , WiFi Integrates 802.3af-compliant PoE circuit (5V/2.5A) USB 2.0 Type A × 4 HDMI × 2, supports 4K 30fps output MicroSD card socket Size 175.0 × 108.0mm	BBR NUC PoE Controller (BBR-NUC) Gigabit Ethernet RJ45 connector , WiFi Integrates 802.3af-compliant PoE circuit (5V/2.5A) USB 2.0 Type A × 4 HDMI × 2, supports 4K 30fps output MicroSD card socket Fan allows speed adjustment and measurement, 5V / 12V Battery parallel 18650 Li-ion battery × 3 Size 175.0 × 108.0mm Warranty 1Year
<b>BBR-BASE-SW</b>	<b>FREE</b>		<b>On Cloud Barbary Management Software 1 system (BBR-BASE-SW)</b>	Barbary Management Software 1 system (BBR-BASE-SW) Warranty 1Year
<b>BBR-TS-LIC</b>	<b>1,150/year</b>		<b>On Cloud Barbary Indoor Tracking Software bundle license 1 gateway - For BBR-GW-BLE5</b>	On Cloud Barbary Indoor Tracking Software bundle license 1 gateway (BBR-TS-LIC) - Subscription 1Year - Warranty 1Year
<b>BBR-ND-LIC</b>	<b>575/year</b>		<b>On Cloud Barbary Locator Node ULR Beacon license 1 node - For BBR-ND-ULR</b>	On Cloud Barbary Locator Node ULR Beacon license 1 node (BBR-ND-LIC) - Subscription 1Year - Warranty 1Year
<b>BBR-CL-LIC</b>	<b>115/year</b>		<b>On Cloud Barbary Indoor Tracking Software Client License 1 client - For Sensor Tag or BT Beacon</b>	On Cloud Barbary Indoor Tracking Software Client License 1 client (BBR-CL-LIC) - Subscription 1Year - Warranty 1Year
<b>SAKER IoT Building Management System Smart Product Solution</b>				
<b>SK-BASE-SW</b>	<b>FREE</b>		<b>On Cloud SAKER Management Software</b> - Develop according to customer requirements - Special Price for Project	Warranty Software 1Year
<b>SK-CONB-LC</b>	<b>10,350/year</b>		<b>On Cloud SAKER Control Board Channel License</b>	Warranty 1Year


## FalCo Solution Access Control & Temperature Screening Terminal & Kiosk

FalCo Solution Co.,Ltd. 47/319, 5th floor, KaiTak Building, Popular Road, Ban Mai Subdistrict, Pak Kret District Nonthaburi Province, 11120 Thailand Tax ID: 0135558013787

Item No.	Price list (Baht) Exc.VAT	Picture	Main Function	Specifications
SK-8CH-LC	920/year		On Cloud SAKER 8 CH High Power Switch License	Warranty 1Year
SK-16CH-LC	1,599/year		On Cloud SAKER 16 CH High Power Switch License	Warranty 1Year
SK-16CH-LC	2,875/year		On Cloud SAKER 32 CH High Power Switch License	Warranty 1Year
SK-API-LC	FREE		SAKER Software API FREE License	Warranty 1Year
SK-CNTL-LN	40,250.00		SAKER Smart Controller	Warranty 1Year
SK-CONB-8	10,925.00		SAKER 8CH High Power Switch (SK-CONB-8) Actuator has 8channels (10A for each channel) and 16A magnetic latching relay. With low power consumption and long lifetime, the module has manual control switches and supports scene and sequence control.	SAKER IoT Modbus RTU DC 12V 10A 8 Channel CH DIN Rail RS485 Relay Module Board with DIN Rail Box for PLC PTZ Camera Motor LED UM72 Warranty 1Year
SK-CONB-16	17,825.00		SAKER 16CH High Power Switch (SK-CONB-16) Actuator has 16channels (10A for each channel) and 16A magnetic latching relay. With low power consumption and long lifetime, the module has manual control switches and supports scene and sequence control.	SAKER IoT Modbus RTU DC 12V 10A 16/32 Channel CH DIN Rail RS485 Relay Module Board with DIN Rail Box for PLC PTZ Camera Motor LED UM72 Warranty 1Year
SK-CONB-32	29,325.00		SAKER 32CH High Power Switch (SK-CONB-32) Actuator has 32channels (10A for each channel) and 16A magnetic latching relay. With low power consumption and long lifetime, the module has manual control switches and supports scene and sequence control.	SAKER IoT Modbus RTU DC 12V 10A 16/32 Channel CH DIN Rail RS485 Relay Module Board with DIN Rail Box for PLC PTZ Camera Motor LED UM72 Warranty 1Year
SK-PWR	1,438.00		DIN Rail Power Supply 12V 4.5A for Smart Power Switch for SAKER16CH (SK-CONB-16) , SAKER32CH (SK-CONB-32)	Warranty 1Year
SK-CBN	2,933.00		Control Center Cabinet (Size 640x920x250)	Warranty 1Year
SK-LRW-GW	8,280.00		SAKER IoT LoRa long range wireless modem (SK-LRW-GW) IOT wireless data transmission LoRa spread spectrum	Working frequency: 915MHz(900~931MHz) Transmitting power: 30 dBm Air data rate: 0.3k~9.6k Test distance: 8000 meter Size:82*62*25 mm Antenna type: SMA-K Communication interface: RS232 / RS485 Warranty 1Year
SK-EPM-SP	5,520.00		Intelligent Electric Power Meter Single Phase (SK-EPM-SP) Single Phase 2 Wire Energy Meter DIN Rail Mounting LCD Backlight Display AC 230V 5-80A	Phase: Single Phase Accuracy Class: 1 Measuring Energy Range: 0.1-99999.9 KWH Output Voltage: 110V/127V/240V AC(option) Operating Temperature: -25°C - +55°C Dimensions: 78.5*36.5mm Certification: CE Current: 5(80)A Warranty 1Year
<b>LAGGAR Single System Monitoring Software</b>				
LAGGAR SW	CALL		LAGGAR System Monitoring Software Monitor Everything in Your Network and Easy to use!We make it simple monitoring, alerting, log, reporting for you. Special Price for Project	Warranty Software & On Site / Remote Free 1Year 
<b>Face + Finger + Card + Passcode Scanner &amp; Access Control</b>				
X7 (>5pcs)	2,350.00		X7 เครื่องสแกนนิ้วมีและตามบัตรเพื่อเปิดประตู Finger Capacity : 500 Card Capacity : 2.000 Operating Temperature : 0°C-40°C Sensor : ZK Optical Sensor Algorithm : Version 10.0 Access Control : card party electric Lock, Alarm, :Door Sensor, Exit button, Door bell Dimension (L*W*H) :88*88*33.6 mm Warranty 2Year	X7 เป็นระบบเปิด - ปิดประตูด้วยระบบลายนิ้วมือ และระบบอ่านบัตรอยู่ในเครื่องเดียวกัน สามารถใช้งานโดยสแกนลายนิ้วมือหรือ ทาบบัตร ประตูก็จะคลายล็อก ใช้งานง่าย มีหลอดไฟ LED ใช้สถานการณ์ทำงานดังเครื่อง เล็กกะทัดรัด ติดตั้งง่าย สะดวกเหมาะที่ติดตั้งทุกที่ ห้องผู้บริหาร ห้องลับ ห้องพิเศษ ที่ไม่ต้องการให้คนที่ไม่เกี่ยวข้องเข้าไปในห้องได้ไม่ได้รับอนุญาต โดยใช้งานได้หลายรูปแบบ
SC105-ID (>5pcs)	4,250.00		SC105-ID เครื่องตามบัตรมีการ์ดเปิดประตู บันทึกเวลาทำงาน มีจอสัมผัส ใช้งานง่าย มี TimeZone และ RS-485 รองรับ 30,000 บัตร (ID Card or Proximity Card) บันทึกรายการเข้า - ออกได้ 80,000 รายการ หน้าจอสี TFT LCD ขนาด 2 นิ้ว มีเมนูให้เลือกได้ทั้งไทยและอังกฤษ สามารถเชื่อมต่อข้อมูลระบบ USB , LAN กำหนดเวลาเข้า - ออก ได้ 50 Time Zone หลอด LED สีเขียวและสีแดงแสดงสถานะ มีเมนูให้เลือกได้ทั้งไทย / อังกฤษ Access control ขนาด 130mm×94mm×52mm Software ZKAccess 3.5 Warranty 2Year	เครื่องตามบัตร มีชื่อ Zkteco รุ่น SC105 เป็นเครื่องอ่านบัตรระบบ RFID คลื่นความถี่ 125 KHz สามารถใช้งานได้กับบัตร Proximity หัวไม้ได้ รองรับบัตรได้ 30,000 ใบ เครื่อง SC105 ใช้เพื่อความคุ้มค่าเปิด-ปิดประตู สามารถใช้งานได้กับระบบ Controller Board Wiegand หรือจะใช้งานเป็นระบบ Standalone โดยไม่ต้องเปิดคอมพิวเตอร์ตลอดเวลา บันทึกการเข้า-ออกได้ 80,000 รายการ หน้าจอสีขนาด 2 นิ้ว มีเสียงตอบรับเป็นภาษาไทย เชื่อมต่อได้หลายรูปแบบ USB Flash Drive, TCP/IP, RS232, RS485 ตัวเครื่องเป็นระบบ Access Control สามารถต่อเข้ากับชุด Electronic Lock ได้ทุกชนิด ตั้งรูปแบบเวลาการเข้าออกได้ 50 แบบ (50 Time Zone) มีระบบพื้นความปลอดภัย Anti Pass-Back มีฟังก์ชันตรวจสอบการเข้า-ออกที่ไม่ถูกต้อง นำพร้อมโปรแกรมตรวจสอบเวลาเข้า-ออกของบุคคล






## FalCo Solution Access Control & Temperature Screening Terminal & Kiosk

FalCo Solution Co.,Ltd. 47/319, 5th floor, KaiTak Building, Popular Road, Ban Mai Subdistrict, Pak Kret District Nonthaburi Province, 11120 Thailand Tax ID: 0135558013787

Item No.	Price list (Baht) Exc.VAT	Picture	Main Function	Specifications
SC405-MF (>5pcs)	6,150.00		<b>SC405-MF (รุ่นใช้ MiFare Card)</b> บัตร,รหัส,บัตร+รหัส รองรับบัตร Mifare : 30,000 รายการบันทึก : 80,000 การสื่อสาร TCP/IP,RS485,USB-Host ควบคุมประตู ล็อคไฟฟ้า,เซ็นเซอร์ประตู,Exit Switch,Alarm หลอด LED สีเขียวและสีแดงแสดงสถานะ Power Supply 12VDC 3A. Software ZKAccess 3.5 ขนาด 143x96x42 mm. Warranty 2Year	<b>ZKTeco SC405 -MF</b> เครื่องงานเปิดประตู และบันทึกเวลาทำงาน ผสมลงไฟฟ้าได้ทุกชนิด เชื่อมต่อได้ทั้ง LAN, Wiegand, RS-485
EFace10 (>5pcs)	4,260.00		<b>EFace10 ZKTeco เครื่องสแกนใบหน้า ลงเวลาทำงาน</b> EFace10 Face Scanner บันทึกใบหน้าได้ 500 คน บันทึกบัตร (ฟังก์ชันเสริม) บันทึกรายการได้ 150,000 รายการ สามารถควบคุมประตูได้ จอสีขนาด 4.3" พร้อม TouchScreen มีช่อง USB FlashDrive สำหรับโอนข้อมูล มีช่อง TCP/IP เพื่อส่งข้อมูลผ่านสาย LAN รองรับ Software: Biotime8, ZKTime.Net Warranty 2Year	EFace10 ZKTeco Standard Time Attendance OS: Linux Memory: 256MB RAM/512MB Flash Communication: TCP/IP, USB Host Face Capacity: 500 Transaction Capacity: 150,000 AC Adapter: 12V 1.5A Operating Temperature: 0°C- 45°C Operating Humidity: 20%-80% Standard Functions: ADMS, Work Code, DST, Self-service Query, Automatic Status Switch, T9 Input, Camera, 9-digit User ID, Multiple Verification Methods, Bell Scheduling Access Control Interface: 3rd Party Electric Lock, Door Sensor, Exit Button Compatibility: ZKTime.Net 4.0 Dimensions(W*H*D): 130 * 119 * 28 (mm) / 130*119*55 (mm)
CMi681S (>5pcs)	5,220.00		<b>เครื่องสแกนลายนิ้วมือ HIP Fingerprint S Series รุ่น CMi 681S</b> Time Attendance - Access Control Standalone Fingerprint Finger 6,000 (6,000 ID Card) Record 160,000 2.8" TFT Graphic DCSV 1A Warranty 2Year	<b>เครื่องสแกนลายนิ้วมือ HIP Fingerprint S Series รุ่น CMi 681S</b> Time Attendance - Access Control Standalone Fingerprint Finger 6,000 (6,000 ID Card) Record 160,000 ID Card Finger / Card / Password / Finger + Card / Finger + Password 2.8" TFT Graphic TCP/IP Access Control ผ่าน Power Box DCSV 1A Size 170x120x35mm. Warranty 2Year
Ci691S (>5pcs)	5,760.00		<b>เครื่องสแกนลายนิ้วมือ HIP Fingerprint รุ่น Ci 691S</b> Time Attendance - Access Control User : 10,000 Finger 10,000 , Record 160,000 ID Card 2.8" TFT Graphic Warranty 2Year	<b>เครื่องสแกนลายนิ้วมือ HIP Fingerprint รุ่น Ci 691S</b> Time Attendance - Access Control User : 10,000 Finger 10,000 , Record 160,000 ID Card Finger / Card / Finger + Card Mode 2.8" TFT Graphic TCP/IP Access Control ผ่าน Power Box DC12V 2A Size 114x114x35mm. Warranty 2Year
CMiF77S (>5pcs)	7,350.00		<b>เครื่องสแกนใบหน้า HIP Face Scan รุ่น CMiF77S</b> Time Attendance - Access Control - Visitor Management - Time 4.0 User : 2,000 Face 2000 , Finger 10,000 , ID Card 2000 , Passcode 2000 Record 200,000 2.8" Touch Screen Warranty 2Year	<b>เครื่องสแกนใบหน้า HIP Face Scan รุ่น CMiF77S</b> Time Attendance - Access Control - Visitor Management - Time 4.0 User : 2,000 Face 2000 , Finger 10,000 , ID Card 2000 , Passcode 2000 Record 200,000 2.8" Touch Screen Identification mode: Finger / Face / Password / Card + Finger / Face + Password / Finger + Card / Face + Card WiFi , TCP/IP Power DC12V 2A Size 188.2x77.7x31.8mm. Option feature (Mifare Card Option) Warranty 2Year
<b>Face Recognition Access Control Time Attendance Device</b>				
FCS-MU86 (>10pcs)	15,096.00		<b>FCS-MU86 QR code scanner, IC card swiping Integrated code scanner QR code access controller</b> Output Interface : RS485, wiegand, Ethernet, relay Indicating Method : Red,green, blue, white indication light Beep Install Method : Wall mounted type RF 13.56mhz Distance <5cm	<b>FCS-MU86 QR code scanner, IC card swiping Integrated code scanner QR code access controller</b> Output Interface : RS485, wiegand, Ethernet, relay Indicating Method : Red,green, blue, white indication light Beep Imaging Sensor : 300,000 pixel CMOS sensor Max Resolution : 640*480b Install Method : Wall mounted type RF 13.56mhz Distance <5cm Product Size : 132*88*21mm <b>QR Code Management Web Application (Option) contact : sale@falco.co.th</b> Warranty 1Year
FCS-105F (>10pcs)	11,000.00		<b>FCS-105F Face &amp; Finger Print &amp; Card (Touch Screen)</b> 5.1inch high-definition IPS screen, resolution854*480 WiFi Module 2.4GHz Card support 125KHz frequency band ID card, support 13.56MHz frequency band Touch Screen Capacitive single touch screen Recognition Speed Fastest 0.3 seconds Recognition distance 0.3m-1.5m Identification record capacity 100,000 Face Capacity 5,000 Fingerprint capacity 3,000 1 RJ45 10M / 100M adaptive Ethernet port , Wiegand interface , Alarm , Magnetic , Door Opening Doorbell Interfaces, RS485 , USB IP65 Warranty 1Year	<b>FCS-105F Face &amp; Finger Print</b> 5.1inch high-definition IPS screen, resolution854*480 Storage 1GB memory +8GB eMMC Camera Binocular, 2.1 million effective pixels, 1920*1080 WDR WiFi Module 2.4GHz WiFi SoC chip, integrated IEEE 802.11b/g/n Card support125KHz frequency band ID card, support 13.56MHz frequency band, ISO-14443 TYPE-AStandard Mifare card, DESFire card, CPU card and ID card UID Touch Screen Capacitive single touch screen Voice playback content can be customized Recognition Speed Fastest 0.3 seconds Recognition distance 0.3m-1.5m Identification record capacity 100,000 Face Capacity 5,000 Fingerprint capacity 3,000 Power Input DC12V/2A 1 RJ45 10M / 100M adaptive Ethernet port , Wiegand interface , Alarm , Magnetic , Door Opening Doorbell Interfaces, RS485 , USB





## FalCo Solution Access Control & Temperature Screening Terminal & Kiosk

FalCo Solution Co.,Ltd. 47/319, 5th floor, KaiTak Building, Popular Road, Ban Mai Subdistrict, Pak Kret District Nonthaburi Province, 11120 Thailand Tax ID: 0135558013787

Item No.	Price list (Baht) Exc.VAT	Picture	Main Function	Specifications
<b>FCS-105 (&gt;10pcs)</b>	<b>21,390.00</b>		<b>FCS-105</b> Display 5-inch IPS HD Screen Dual cameras 2MP, 1920*1080 Support Mifare 13.56MHz. , WiFi Module Recognition distance 0.5~1.5 meters Face Capacity 10,000pcs library Storage 80,000 capture records Recognition time <0.2sec Power out DC12V/2A	<b>FCS-105</b> Display 5-inch IPS HD Screen Dual cameras 2MP, 1920*1080 WDR 120db Support Mifare 13.56MHz. , WiFi Module Recognition distance 0.5~1.5 meters 1Gmemory+ 8G eMMC Face Capacity 10,000pcs library Storage 80,000 capture records Recognition time <0.2sec 1 RJ45 10M / 100M adaptive Ethernet port 1ch Wiegand interface input/output Power out DC12V/2A Waterproof IP42 Size 205(L) * 95 (W) * 24.5(T) mm Warranty 1Year
<b>FCS-105M</b>	<b>25,185.00</b>		<b>FCS-105M Palm Attendance</b> Screen 4.3"Touch Screen Screen resolution 480*272 Recognition mode Fingerprint, face, palm, IC, password Recognition Speed Fastest 0.3 seconds Recognition distance 0.5m-4.0m Data Capacity 5000 facial data, 3000 fingerprint data, 3000 palm print data, 5000 passwords, 5000 cards Attendance log capacity 1,000,000 logs	<b>FCS-105M Palm Attendance</b> Screen 4.3"Touch Screen Screen resolution 480*272 Recognition mode Fingerprint, face, palm, IC, password Dual camera 1.0M RGB camera + 1.0 Infrared camera Recognition Speed Fastest 0.3 seconds Recognition distance 0.5m-4.0m supporting palm / palm + face / palm + fingerprint / face + fingerprint / palm + fingerprint + face and other mixed verification methods Interface Wired TCP/IP, 1*USB 2.0, Wiegand 26/34 output Data Capacity 5000 facial data, 3000 fingerprint data, 3000 palm print data, 5000 passwords, 5000 cards Attendance log capacity 1,000,000 logs Dimension 90*28*189mm Warranty 1 Year
<b>FCS-108 (&gt;10pcs)</b>	<b>26,335.00</b>		<b>FCS-108 8 Inch HD IPS Screen</b> Face Recognition Biometric Machine Dual Core Processor(Hi3516D V300)+ 1G memory + 16G flash Len 6mm Effective Pixel : 2MP, 1920*1080 Support Mifare 13.56MHz. Recognition Distance : 0.5~1.5 meters, depends on lens Recognition Time : Less than 0.5 seconds Storage Capacity : 160,000 capture records Face capacity 24,000 RS485 , USB Interface Waterproof IP66	<b>FCS-108 8 Inch HD IPS Screen</b> Face Recognition Biometric Machine Dual Core Processor(Hi3516D V300)+ 1G memory + 16G flash Len 6mm Effective Pixel : 2MP, 1920*1080 Support Mifare 13.56MHz. Recognition Distance : 0.5~1.5 meters, depends on lens Recognition Time : Less than 0.5 seconds Storage Capacity : 160,000 capture records Face capacity 24,000 Network Interface : 1 RJ45 10M / 100M adaptive Ethernet port RS485 , USB Interface Waterproof IP66 Size 260 (L) * 136 (W) * 26 (T) mm Power DC12V/2A Warranty 1 Year
<b>FCS-108TS (&gt;10pcs)</b>	<b>30,475.00</b>		<b>FCS-108TS (Touch Screen)</b> 8' Inch Touch Screen Face Recognition Access Control Terminal Effective pixels 2MP, 1920*1080 WiFi 2.4GHz frequency band, IEEE802 b/g/n Support reading 13.56MHz, 125KHz, Recognition distance 0.5~2.5 meters Recognition time Less than 0.3 seconds Storage capacity 160,000 capture records Face capacity 24,000	<b>FCS-108TS (Touch Screen)</b> 8' Inch Touch Screen Face Recognition Access Control Terminal Dual Core Processor+ 1G memory + 16G flash WiFi 2.4GHz frequency band, IEEE802 b/g/n protocol; 5GHz frequency band, IEEE802 a/n/ac protocol Support reading 13.56MHz, 125KHz, 915MHz frequency band signals Support real time liveness detection face recognition time is less than 0.3s Support 24,000 face matching library and 160,000 face recognition records 8-inch touch screen, no streaking and delay Support 2D noise reduction, 3D noise reduction Recognition distance 0.5~2.5 meters, depends on lens Recognition time Less than 0.3 seconds Storage capacity 160,000 capture records Face capacity 24,000pcs 1 RJ45 10M / 100M adaptive Ethernet port Warranty 1 Year
<b>FCS-1010 (&gt;5pcs)</b>	<b>56,235.00</b>		<b>FCS-1010</b> 10 Inch Face Recognition Access Control Terminal Recognition distance 0.5~2.5 meters Recognition time Less than 0.5 seconds Built-in QR code reader Built-in IC card reader Storage 80,000 snapshot records Face Capacity 30,000 Interface 1 RJ45 10M / 100M adaptive Ethernet port	<b>FCS-1010</b> 10 Inch Face Recognition Access Control Terminal Dual-core processor + 1G RAM + 8G EMMC Binocular, 2.1 million effective pixels, 1920*1080 Recognition distance 0.5~2.5 meters Recognition time Less than 0.5 seconds Storage 80,000 snapshot records Face Capacity 30,000 Interface 1 RJ45 10M / 100M adaptive Ethernet port Built-in QR code reader Built-in IC card reader Abundant hardware interfaces (I/O, WG26, WG34, RJ45, door sensor, door opening, RS485) Warranty 1 Year
<b>FCS-AD08TS (&gt;10pcs)</b>	<b>63,250.00</b>		<b>FCS-AD08TS Android 9.0 Tablet SIM Card With Mobile Fingerprint Handheld Device</b> 8 inch touch screen 1280*800, IPS Android 9.0 Rugged IP65 Front camera 2M pixels, Rear camera 13M pixels Support: 4G, GPS, Wifi, Bluetooth ,NFC Wifi 802.11 b/g/n Micro USB, Support OTG , Bluetooth 4.0 IP65 Waterproof, fall prevention,dust prevention,1.5 meter drop resistance Touch Panel:Capacitive panel, multi-point touch, G+G Battery DC 3.7V/8000mAh	<b>FCS-AD08TS Android 9.0 Tablet SIM Card With Mobile Fingerprint Handheld Device</b> 8 inch touch screen 1280*800, IPS CPU MTK6761 cortex-A7 1.5GHz Quad core Android 9.0 Rugged IP65 Front camera 2M pixels, Rear camera 13M pixels Support: 4G, GPS, Wifi, Bluetooth ,NFC Wifi 802.11 b/g/n Micro USB, Support OTG , Bluetooth 4.0 Fingerprint Sensor: TCS1 (others can be customize) IP65 Waterproof, fall prevention,dust prevention,1.5 meter drop resistance Touch Panel:Capacitive panel, multi-point touch, G+G Battery DC 3.7V/8000mAh G-sensor 3 axis Built-in microphone , Built-in stereo speaker 8Ω/1.5W*2 TF 1x mini SD card up to 64G Dimension 254(L)*154(W)*25.2(H)mm Wall-mounted holder & Kiosk holder is optional Warranty 1 Year

# FalCo Solution Access Control & Temperature Screening Terminal & Kiosk

FalCo Solution Co.,Ltd. 47/319, 5th floor, KaiTak Building, Popular Road, Ban Mai Subdistrict, Pak Kret District Nonthaburi Province, 11120 Thailand Tax ID: 0135558013787

Item No.	Price list (Baht) Exc.VAT	Picture	Main Function	Specifications
FCS-S08HP (>5pcs)	70,725.00		<b>FCS-S08HP High Performance Face Recognition</b> High Performance Face Recognition Device 8Inch Touch Screen 1280*800 HD IPS Touch Screen Aluminium Alloy frame and pillar for durability Protection Level IP64, Can be used Outdoor	<b>FCS-S08HP High Performance Face Recognition</b> CPU 4 cores, 1.8GH, Android 9.0 Memory 2GB RAM, 16GB ROM LED Filling light Ic card reader (Optional) Support wired, wireless (2.4G Wi-Fi) Dual Camera 2.0M (RGB Camera); 1.3M (Infrared Camera) Wide dynamic camera Wide dynamic automatic , White balance automatic Aperture 4m. Focal Length 0-2m. Support Wiegand 26/34 input/output , RS232 , NC,NO and COM QR Code, HDMI, HID, Health Code, 4G, Printer (Optional) Interface USB2.0 RJ45 Face Detection 20,000 Capacity Support Detecting and tracking 5 people at the same time 1:N Face Recognition Recognition distance Support (0.5- meters) Protection Level IP65 Installation method Turnstile, Wall mounted, Desktop, Floor Type Devices Size 370(L)*125(W)*24.5(H)mm Warranty 1Year
<b>Smart Face Recognition Temperature Device</b>				
K3 (>20pcs)	1,300.00		<b>เครื่องวัดอุณหภูมิฝ่ามือ Falco K3</b> -เครื่องวัดอุณหภูมิฝ่ามือและหน้าผาก (ใช้คัดกรองผู้พบ Covid-19 ก่อนเข้าทำงาน) -ความแม่นยำในการวัดอุณหภูมิสูง: สูงถึง± 0.2 °C (สำหรับการใช้งานในช่วงอุณหภูมิ 34 – 45 องศาเซลเซียส) -Falco K3 มีจอแสดงผลแบบระบบสัมผัสสำหรับการวัดอุณหภูมิที่กว้าง: 10 – 50 °C -แจ้งเตือนอัตโนมัติเมื่ออุณหภูมิเกินกำหนด ด้วยเสียงและไฟแฟลช -เครื่องจะปิดเองอัตโนมัติภายใน 5 วินาทีเมื่อไม่ใช้งาน -มีคริสตัลเลอร์ฆ่าเชื้อล้างข้อ 20 เครื่องในครั้งแรก -รับประกันตัวเครื่อง 1 ปี	<b>Falco K3 Infrared Thermometer For Head Thermoscan</b> -เครื่องวัดอุณหภูมิหน้าผาก หรือ เครื่องวัดอุณหภูมิฝ่ามือ (ใช้คัดกรองผู้พบ Covid-19 ก่อนเข้าทำงาน) -ความแม่นยำในการวัดอุณหภูมิสูง: สูงถึง± 0.2 °C (สำหรับการใช้งานในช่วงอุณหภูมิ 34 – 45 องศาเซลเซียส) -Falco K3 มีจอแสดงผลแบบระบบสัมผัสสำหรับการวัดอุณหภูมิที่กว้าง: 10 – 50 °C -แจ้งเตือนอัตโนมัติเมื่ออุณหภูมิเกินกำหนด ด้วยเสียงและไฟแฟลช -เครื่องจะปิดเองอัตโนมัติภายใน 5 วินาทีเมื่อไม่ใช้งาน -เมื่อตรวจจับอุณหภูมิสูงเกินค่าที่กำหนดจะมี ไฟ LED พรหมพริบเตือน และมีเสียง คัด คัด (เตือนนาน 10 วินาที) -ความไวของการตรวจวัดอุณหภูมิ: 0.5 วินาที -แสดงหน่วยอุณหภูมิได้ ทั้งองศาเซลเซียส และองศาฟาเรนไฮต์ -เครื่องวัดอุณหภูมิหน้าผากและฝ่ามือ -Falco K3 ใช้สำหรับบันทึกคนเข้าออกภายในอาคารได้ นับได้สูงสุด 999 คน -ขนาดเล็กกระทัดรัด น้ำหนักเบา พกพาสะดวก -ระยะการวัด : ยืนห่างจากจุดวัด 5 – 10 เซนติเมตร -หน้าจอสั่งแสดงผลแบบมัลติจี้ ดิจิตอล ( 7-Segment 3 ตำแหน่ง ) -ขนาด : 17 x 11.5 x 14 เซนติเมตร -น้ำหนัก : 350 กรัม -แหล่งจ่ายไฟ : USB DC 4.2-5V ใช้สาย USB พร้อมถ่านชาร์ตในเครื่อง -แบตเตอรี่ลิเธียม และ แบตเตอรี่ไฟฟ้ -เครื่องวัดอุณหภูมิหน้าผากและฝ่ามือ Falco K3 ไม่ต้องสัมผัส สัมผัสด้วย คัดกรองได้เร็ว แจ้งเตือนด้วยเสียง เคลื่อนย้ายสะดวกเหมาะในการติดตั้งทั้ง ร้านอาหาร ร้านขายสินค้า ร้านค้า ภายในห้างสรรพสินค้า ออฟฟิศ โรงพยาบาล วัด สนามบิน อาคารสำนักงาน สถานศึกษา รวมถึงใช้คัดกรองในสถานศึกษา เป็นต้น <b>รับประกัน 1 ปี เปลี่ยนเครื่องใหม่ฟรี</b>
K9 Pro (>10pcs)	2,300.00		<b>เครื่องวัดอุณหภูมิฝ่ามือ พร้อมจ่ายแอลกอฮอล์ล้างมือ Falco K9 Pro</b> -จ่ายแอลกอฮอล์ล้างมืออัตโนมัติ -Measuring range : ±0.2 (35 – 45 °C) -สัญญาณเตือน: มีไฟและเสียงเตือน (Alarm Flashing+bleeping"DIDIDI") -ระยะการวัด: 5-10cm -หน้าจอ: LCD -บรรจุของเหลวได้มากถึง 1000 ml. -การติดตั้ง: แขวน, ติดกับขาตั้ง -สมัครสิทธิเดอริชั่นล้างข้อ 10 เครื่องในครั้งแรก -รับประกันตัวเครื่อง 1 ปี	<b>Falco K9 PRO New Arrival hand free Automatic alcohol spray thermometer K9 pro</b> -จ่ายแอลกอฮอล์ล้างมืออัตโนมัติ -Measuring range : ±0.2 (35 – 45 °C) -สัญญาณเตือน: มีไฟและเสียงเตือน (Alarm Flashing+bleeping"DIDIDI") -ระยะการวัด: 5-10cm -หน้าจอ: LCD -บรรจุของเหลวได้มากถึง 1000 ml. -การติดตั้ง: แขวน, ติดกับขาตั้ง -อุณหภูมิในการทำงาน 10°C ~ 40°C (แนะนำ15°C – 35°C) -ช่วงการวัด: 0 – 50°C -การคอมสเอง : 0.5s -เตรียมการทำงาน : ภายใน 5 วินาที มีไดนามิกรูปพร้อมแสงสีขาว -ขนาด: 119x 133 x 280 mm -วัสดุ ABS -ชนิดของเหลวที่บรรจุ : แอลกอฮอล์ทำความสะอาดมือหรือแอลกอฮอล์ฆ่าเชื้อชนิดน้ำ -Mounting type : Wall-hanging, Tripod-fixed,floor stand Support 5 Language -แบตเตอรี่ และ Adaptor + สายชาร์ตฟรี -รับประกัน 1 ปี เปลี่ยนเครื่องใหม่ฟรี
FCS-S02T (>10pcs)	25,185.00		<b>FCS-S02T Face Temperature &amp; Face Recognition</b> 7 Inch IPS LCD Screen Temperature Detection Face database 30,000pcs Resolution 1024*600 Temperature error range ±0.3°C Face recognition distance: 0.5-1.5M	<b>FCS-S02T Face Temperature &amp; Face Recognition</b> Face Recognition, Face Capture,Face Comparison , Face Temp. -Support data output and Management -Complete face capture, recognition, temperature records -Temperature Detection -Fever Warning, Mask Detection -Face database 30,000pcs -Support date import and output -Aircraft-grade aluminum and 7 inch ISP LCD screen -Resolution 1024*600 -Easy-operation to connect to access control:Configure personnel access control permissions -Application Scenarios: school, community, company, office building, super market, hotel, station etc. -More Secure : Non-contact forehead temperature detection to prevent cross-infection -High Precision: temperature detection distance 0.5-1M,0.75M is best -Temperature error range ±0.3°C -More Efficient: face recognition distance: 0.5-1.5M -Recognition Speed/Accuracy: 200ms, 99.5% -Support live detection, avoid photo and video and other deceptive means -Apply for a dealer minimum order 10pcs in the first time. -Warranty 1Year

## FalCo Solution Access Control & Temperature Screening Terminal & Kiosk

FalCo Solution Co.,Ltd. 47/319, 5th floor, KaiTak Building, Popular Road, Ban Mai Subdistrict, Pak Kret District Nonthaburi Province, 11120 Thailand Tax ID: 0135558013787



Item No.	Price list (Baht) Exc.VAT	Picture	Main Function	Specifications
FCS-105T (>10pcs)	30,935.00		<b>FCS-105T Face Recognition &amp; Temperature Screening Touch Screen , WIFI</b> 4.3 Inch Face Recognition Effective pixels 2.1 megapixels, 1920*1080 measurement accuracy ±0.3°C temperature resolution 0.1°C Temperature measuring distance ≤50cm response time 300ms Storage Capacity 60,000 Face Capacity 20,000 Network interface RJ45 10M / 100M Warranty 1 Year	<b>FCS-105T Face Recognition &amp; Temperature Screening Touch Screen , WIFI</b> 4.3 Inch Face Recognition Effective pixels 2.1 megapixels, 1920*1080 Dual camera 1920*1080 WIFI IEEE 802.11b/g/n标准 - 2.4GHz. 1Mbps-150Mbps Bluetooth Optional. 8DPSK,n/4DQPSK, GFSK. 1Mbps-2,3Mbps Touch Screen Optional. support. Capacitive multitouch screen measurement accuracy ±0.3°C temperature resolution 0.1°C Temperature measuring distance ≤50cm response time 300ms Storage Capacity 60,000 Face Capacity 20,000 Network interface RJ45 10M / 100M Output from one waygen interface, input from one waygen interface Screen resolution 480*272 Screen size 4.3 inch Warranty 1 Year
FCS-S08T (>10pcs)	37,375.00		<b>FCS-S08T 8-inch IPS HD (Temperature measurement)</b> 8-inch IPS full-view HD display, no streaking and delay Measurement range 16°C - 40°C (Indoor without wind) Measurement accuracy ±0.3°C ≤40cm Temperature measurement distance Measurement response time 300ms Dual Core Processor+ 1G memory + 16G flash Recognition distance 0.3~1.5 meters Recognition time Less than 0.5 seconds Support 24000 face matching library and 160,000 face recognition record	<b>FCS-S08T 8-inch IPS HD (Temperature measurement)</b> 8-inch IPS full-view HD display, no streaking and delay Measurement range 16°C - 40°C (Indoor without wind) Measurement accuracy ±0.3°C ≤40cm Temperature measurement distance Measurement response time 300ms body temperature measurement and high temperature alarm Dual Core Processor+ 1G memory + 16G flash Recognition distance 0.3~1.5 meters Recognition time Less than 0.5 seconds Support 24000 face matching library and 160,000 face recognition record 3D noise reduction and fog-passing technology makes the monitoring picture under low illumination more clear and delicate Support video brightness, contrast, hue, saturation, gamma adjustment Waterproof IP65 Size 274(L) * 140.96 (W) * 108.3 (T) mm Warranty 1 Year
FCS-S08TCQ (>10pcs)	47,093.00		<b>FCS-S08TCQ 8-inch IPS HD (Temperature measurement)</b> 8-inch IPS full-view HD display, no streaking and delay Support QR Code Support IC Card 13.56MHz. Measurement range 16°C - 40°C (Indoor without wind) Measurement accuracy ±0.3°C ≤40cm Temperature measurement distance Measurement response time 300ms Dual Core Processor+ 1G memory + 8G flash Recognition distance 0.3~1.5 meters Recognition time Less than 0.5 seconds Support 24000 face matching library and 160,000 face recognition record	<b>FCS-S08TCQ 8-inch IPS HD (Temperature measurement)</b> 8-inch IPS full-view HD display, no streaking and delay Support QR Code , Support IC Card 13.56MHz. Measurement range 16°C - 40°C (Indoor without wind) Measurement accuracy ±0.3°C ≤40cm Temperature measurement distance Measurement response time 300ms body temperature measurement and high temperature alarm Dual Core Processor+ 1G memory + 16G flash Recognition distance 0.3~1.5 meters Recognition time Less than 0.5 seconds Support 24000 face matching library and 160,000 face recognition record 3D noise reduction and fog-passing technology makes the monitoring picture under low illumination more clear and delicate Support video brightness, contrast, hue, saturation, gamma adjustment Waterproof IP65 Warranty 1 Year
FCS-S05T (>10pcs)	33,350.00	 <b>OUT OF STOCK</b>	<b>FCS-S05T Face Recognition, Face Comparison, Mask Detection, Real Face Detection, Mask Recognition.</b> 10.1 inch ISP LCD screen 1280*720 Full screen recognition  Face recognition distance: 0.5-2M Recognition Speed/Accuracy: 200ms, 99.5% Recognition angle: Horizontal 60°, vertical 35° Face database 30000pcs Temperature detection distance 0.7-1.2M Temperature Measuring Range ±35°C-42°C, Temperature error range ±0.3°C; 16GB eMMC Support binocular Real Face detection function, effectively offline recognition, 50000 offline records MAX	<b>FCS-S05T Face Recognition, Face Comparison, Mask Detection, Real Face Detection, Mask Recognition.</b> HDR Ultra Dual Camera: Infrared Camera: 2MP, 4.5mm lens Video Camera: 2MP SONY Sensor Operating system: Linux Dual-core ARM Cortex-A7, NPU 1.2T, DDR3 1GB Wifi: 2.4G/5.8G,IEEE 802.11b/g/n,802.11a/ac LED Light: Infrared Light, White Light Screen: 10.1 inch ISP LCD screen, resolution 1280*800 Interface: RJ45 RS485, Wiegand input and output ,Reset key , Alarm out,USB Support WIFI ,Swip card ,SD card and Bluetooth <b>4G Function is Option Add 5,500Baht</b> Operating temperature:-10-50°C Application Scenarios: school, community, company, office building,etc. Rated voltage: DC 12V input Panel size: 149*78.2*452.9 Warranty 1Year
FCS-S03T (>10pcs)	21,735.00	 <b>OUT OF STOCK</b>	<b>FCS-S03T Face Recognition, Face Comparison, Mask Detection, Real Face Detection, Mask Recognition.</b> 5 inch ISP LCD screen 1280*720 Face database 2000pcs Face recognition distance: 0.5-0.75M	<b>FCS-S03T Face Recognition, Face Comparison, Mask Detection, Real Face Detection, Mask Recognition.</b> Include both wall and table bracket Dual Camera: Infrared Camera: 2MP, 2.8mm lens Video Camera: 2MP SONY Sensor, 1920*1080@30fps, 4.3mm lens Operating system: Linux AI processor:Cortex-A7,NPU 0.6TCortex-A7. NPU 0.6T DDR3 256MB, EMMC 4GB Wifi: 2.4G/5.8G,IEEE 802.11b/g/n,802.11a/ac LED Light: Infrared Light, White Light Interface: RS485, Wiegand, RS232, RJ45, Relay output, Reset key , RS485, TF card slot Rated voltage: DC 12V input Panel size: 167x13.8mm Weight: 1.2kg Warranty 1Year

### Thermal IP Camera & Face Recognition



# FalCo Solution Access Control & Temperature Screening Terminal & Kiosk

FalCo Solution Co.,Ltd. 47/319, 5th floor, KaiTak Building, Popular Road, Ban Mai Subdistrict, Pak Kret District Nonthaburi Province, 11120 Thailand Tax ID: 0135558013787



Item No.	Price list (Baht) Exc.VAT	Picture	Main Function	Specifications
<b>TMFRAI01</b> (>5pcs)	<b>93,225.00</b>		<b>FCS-TMFRAI</b> CPU RK3288, quad-core, clocked at 1.8GHz Thermal imaging resolution 160*120 Temperature measurement range 35°C~42°C Temperature measurement accuracy can reach ±0.3°C Temperature calibration built-in black body, automatic calibration Measuring time <1 second Measuring distance within 3 meters, the optimal distance is 1~2 meters Face database standard 50,000 Network 1*RJ45, 1*micro USB, 1*HDMI	<b>FCS-TMFRAI</b> CPU RK3288, quad-core, clocked at 1.8GHz Thermal imaging resolution 160*120 Temperature measurement range 35°C~42°C Temperature measurement accuracy can reach ±0.3°C Temperature calibration built-in black body, automatic calibration Microbolometer vanadium oxide Measuring time <1 second Measuring distance within 3 meters, the optimal distance is 1~2 meters Temperature measurement mode face recognition mode: detects the temperature of the whole face, and can recognize locally registered persons Face recognition distance within 3 meters Face database standard 50,000 Network 1*RJ45, 1*micro USB, 1*HDMI Algorithm : Sense time SenseNebulaSDK_V4.2.0 Face character 3.1.0 Support mask detection and Respirator detection, support colour face recognition
<b>S5003T</b> (>5pcs)	<b>67,735.00</b>	 <b>OUT OF STOCK</b>	<b>FCS-S5003T Bullet Thermal Camera</b> Picture-in-picture preview Face Detection Automatic Face tracking & measuring temperature Face Capture and screening Face snapping support 30 faces detection simultaneous Accurate temperature 5-8 faces Built-in 50,000 face database Support multi-person measurements up to 1-3m distances Fast and Non-contact Body Temperature Detection Temperature-anomaly alarm Highly accurate temperature measurement within ±0.5 °C, with black body ±0.3 °C	<b>FCS-S5003T Bullet Thermal Camera</b> Thermal IP Camera: Thermal Module: Resolution 256x192,FOV. 56° x 42°, NETD Less than 60 mK (@25°C,F#=1.1), F1.0 Video Camera: 1/2.8" SONY IMX335, Hisilicon SoC, HDR, Starlight Main Stream: 4MP@30fps,5MP@20fps,2MP@30fps With Internal POE & External SD Card Slot Board Lens 3.6mm Interface: Built in Mic and Speaker, RS485,Reset key,Alarm I/O, Audio I/O Power DC 12V Input Size: 239.53x102.96x84.7mm Weight: 1.4Kgs Warranty 1Year

## Controller Weigand - Access Control - Door Lock


<b>KR100M</b> (>5pcs)	<b>520.00</b>		<b>เครื่องควบคุมประตู 2 สี ZK Teco รุ่น KR100M</b> LED indicator 2 Color LED Indicators (Red and Green) Material ABS+PC with texture Dimension: (WxHxT) mm 116x75x17.3 Weight 120g Index of Protection IP65 Warranty 1Year	Read Range KR100M Up to 5 CM Reading time ( Card ) 300 ms Power DC 6-14V / Max.70mA Input Port 2ea (External LED Control, External Buzzer Control) Output Card Format 34bit Weigand (M) Output Pin Format 8 bits Beeper yes Operating temperature "-20° to +65°C" Operating Humidity 10% to 90% (relative humidity non-considered)																											
<b>C3-200 Package B</b>	<b>7,650.00</b>		<b>Zkteco C3-200 Package B IP Panels For Access Control</b> Set IP-Based Door Access Control Panel A package of C3-200 including Metal box and PSU (Power Supply Unit) ควบคุมประตู : 2 ประตู รองรับบัตร RFID : 30,000 รายการบันทึก : 100,000 การเชื่อมต่อ : Lan, RS485 รองรับที่อ่าน Weigand : 4 ฟุต ส่วนเสริม : Wi-Fi Warranty 2Year	<b>Optional Accessories</b> 																											
<b>InBio260 Package B</b> (>3pcs)	<b>12,480.00</b>		<b>InBio260 Package B เครื่องควบคุมประตู</b> ควบคุมประตูเปิด-ปิดประตู 2 ประตู รองรับลายนิ้วมือได้ 3,000 ลายนิ้วมือ รองรับบัตรได้ 30,000 ใบ สามารถจับกับขั้วหลอดได้ 100,000 รายการ การเชื่อมต่อแบบ TCP/IP และ RS-485 Warranty 1Year	<table border="1"> <thead> <tr> <th>Item</th> <th>Description</th> <th>Quantity</th> </tr> </thead> <tbody> <tr> <td>IP65-100/200/400 Package B</td> <td>Control Panel</td> <td>1 ea</td> </tr> <tr> <td></td> <td>Metal Case</td> <td>1 ea</td> </tr> <tr> <td>20P030300</td> <td>Power Supply (DC12V/5A, Available to Charge for Battery Backup)</td> <td>1 ea</td> </tr> <tr> <td>FR101</td> <td>Display for Card</td> <td>1 ea</td> </tr> <tr> <td></td> <td>Key for Metal Case</td> <td>2 ea</td> </tr> <tr> <td>2KAccess CD</td> <td>Access Software for Control Panel, User Manual</td> <td>1 ea</td> </tr> <tr> <td>Global Weight</td> <td>35.5 (kg)</td> <td></td> </tr> <tr> <td>Net</td> <td>3500x400x100x3000mm</td> <td></td> </tr> </tbody> </table>	Item	Description	Quantity	IP65-100/200/400 Package B	Control Panel	1 ea		Metal Case	1 ea	20P030300	Power Supply (DC12V/5A, Available to Charge for Battery Backup)	1 ea	FR101	Display for Card	1 ea		Key for Metal Case	2 ea	2KAccess CD	Access Software for Control Panel, User Manual	1 ea	Global Weight	35.5 (kg)		Net	3500x400x100x3000mm	
Item	Description	Quantity																													
IP65-100/200/400 Package B	Control Panel	1 ea																													
	Metal Case	1 ea																													
20P030300	Power Supply (DC12V/5A, Available to Charge for Battery Backup)	1 ea																													
FR101	Display for Card	1 ea																													
	Key for Metal Case	2 ea																													
2KAccess CD	Access Software for Control Panel, User Manual	1 ea																													
Global Weight	35.5 (kg)																														
Net	3500x400x100x3000mm																														
<b>Door Lock Set</b> (>3pcs)	<b>4,425.00</b>		<b>ZKteco ชุดลิคต ชุดกลอนเปิด-ปิด ประตูไฟฟ้า (สำหรับประตูบานสวิง)</b> Power Supply 12V 5A สำหรับจ่ายไฟให้ชุดกลอนแม่เหล็ก 600ปอนด์ Battery ขนาด 12V 7.5A สามารถสำรองไฟให้ชุดกลอนแม่เหล็ก 600ปอนด์ มีไฟแสดงสถานะ และเซนเซอร์ตรวจสอบการล็อก ชุด LZ สำหรับแม่เหล็ก 600ปอนด์ สวิตช์ No Touch สำหรับเปิดประตูโดยไม่ต้องสัมผัส Warranty 1Year																												
<b>PS902B</b>	<b>1,275.00</b>		<b>ชุด Power Supply 12V 5A สำหรับจ่ายไฟให้ชุดกลอนแม่เหล็ก 600ปอนด์</b> <b>Power Supply 12 Vdc. 5 Amp</b>																												
<b>Battery12V</b>	<b>675.00</b>		<b>Battery ขนาด 12V 7.5A สามารถสำรองไฟให้ชุดกลอนแม่เหล็ก 600ปอนด์</b> <b>Battery 7.0 Ah</b>																												
<b>LM2805 LMB280</b>	<b>1,800.00</b>		<b>กลอนแม่เหล็ก 600ปอนด์ มีไฟแสดงสถานะ และเซนเซอร์ตรวจสอบการล็อก และ ชุด LZ สำหรับแม่เหล็ก 600ปอนด์</b> <b>Magnetic 600lb + LZ Bracket</b>																												

## FalCo Solution Access Control & Temperature Screening Terminal & Kiosk





FalCo Solution Co.,Ltd. 47/319, 5th floor, KaiTak Building, Popular Road, Ban Mai Subdistrict, Pak Kret District Nonthaburi Province, 11120 Thailand Tax ID: 0135558013787

Item No.	Price list (Baht) Exc.VAT	Picture	Main Function	Specifications
TLEB102	675.00		สวิตช์ No Touch สำหรับเปิดประตูโดยไม่ต้องสัมผัส Exit Swich No Touch	
MF-Card (>100pcs)	20.00		MiFare Card 0.8mm. CARD MIFARE บัตร MIFARE ความถี่ 13.56MHz. บาง 0.8 มม. ใช้กับระบบฝังการ์ดได้	



### Floor Stand

TB060 (>5pcs)	4,025.00		Floor Pole bracket, <b>60CM</b> Material:Aluminum Alloy and Iron	2xUSB 1x LED lightStand size: 283(L)x260(W)x600(H)mm Weight: 7.6Kgs
TB110 (>5pcs)	5,175.00		Floor Pole bracket, <b>110CM</b> Material:Aluminum Alloy and Iron	2xUSB 1x LED lightStand size: 283(L)x260(W)x1100(H)mm Weight: 10.7Kgs

### FCS Face Scan on Cloud Management Solution

FSC1	1,950.00		FCS Face Management on CLOUD 1 Year - 1 Face Scan Device	FCS Face Management on CLOUD 1 Year - 1 Face Scan Device
FSC100	4,500.00		FCS Time Attendance on CLOUD 1 Year - 100 Account User	FCS Time Attendance on CLOUD 1 Year - 100 Account User
FSC500	6,500.00		FCS Time Attendance on CLOUD 1 Year - 500 Account User	FCS Time Attendance on CLOUD 1 Year - 500 Account User
FSC1000	8,500.00		FCS Time Attendance on CLOUD 1 Year - 1000 Account User	FCS Time Attendance on CLOUD 1 Year - 1000 Account User

### Smart WiFi Camera

FCSAC04 (>10pcs)	9,775.00		<b>FCSAC04 Smart WiFi PTZ Camera</b> - 2MP 1080P , WiFi IEEE802.11b/g/n , 2Way Audio - PTZ : 270 Horizontal , 90 Tilt - Guard Point : 6 Points - SD Card Slot 128GB - Free Programm Support Smart Phone - Housing IP65 - Power DC12V/1A - Warranty 1Year	FCSAC04 Smart WiFi PTZ Camera - 2MP 1080P - WiFi IEEE802.11b/g/n , Range 350m. - 2Way Audio - Focus 2.8mm - Motion Detection Alarm - PTZ : 270 Horizontal , 90 Tilt - Guard Point : 6 Points - Night Vision Infrared : 15m. - Day/Night Color/B&W (IR-CUT) - CDS Auto Control - Antenna 3dbi - SD Card Slot 128GB - Free Programm Support Smart Phone - Housing IP65 - Power DC12V/1A - Warranty 1Year
FCSAC904G (>10pcs)	10,465.00		<b>FCSAC904G Solar IP Camera 4GLTE or WiFi Module</b> - 2MP 1080P , 4G LTE4G - WiFi IEEE802.11b/g/n (FCSAC90WF) model - 2Way Audio - PTZ : 270 Horizontal , 90 Tilt - SD Card Slot 128GB - Free Program Support Smart Phone - Housing IP65 - Power DC5V/2A or 18650 Battery Powered - Warranty 1Year	FCSAC904G Solar IP Camera 4GLTE or WiFi Module - 2MP 1080P - Video Output 4G Network - 4G LTE4G-Nano SIM , LTE-FDD:B1/3/5/8 , LTE-TDD:B38/39/40/41 - WiFi IEEE802.11b/g/n (FCSAC90WF) model - 2Way Audio - Focus 3.6mm - Motion Detection Alarm - PTZ : 270 Horizontal , 90 Tilt - Night Vision Infrared : 15m. - Day/Night Color/B&W (IR-CUT) - CDS Auto Control - SD Card Slot 128GB - Free Program Support Smart Phone - Housing IP65 - Power DC5V/2A or 18650 Battery Powered - Warranty 1Year

## FalCo Solution Access Control & Temperature Screening Terminal & Kiosk

FalCo Solution Co.,Ltd. 47/319, 5th floor, KaiTak Building, Popular Road, Ban Mai Subdistrict, Pak Kret District Nonthaburi Province, 11120 Thailand Tax ID: 0135558013787

Item No.	Price list (Baht) Exc.VAT	Picture	Main Function	Specifications
<b>Turnstiles &amp; Swing Gate Device</b>				
<b>CMC301</b> (>3pcs)	<b>47,600.00</b>		<b>ระบบประตูโรงงาน Turnstile รุ่น CMC301</b> Power AC220V+-10V, 50Hz/AC110+-10V,60Hz Passage Width : <=600mm Power Consumption : 100W Communication Interface RS485 (Distance : <=1200) Material : Housing - 304 stainless steel arm - stainless steel Environment : Indoors or outdoors with shed	<b>ระบบประตูโรงงาน Turnstile รุ่น CMC301</b> Power Supply 220VAC 50Hz Temperature -15°C to +60°C Humidity<math>\leq 90\%</math> Working Voltage of motor 24VDC Max Power consumption 100 W Passage Width $\leq$ 600mm Passing Speed 40 people/min (Access Control) Control interface Relay signal input Material Stainless Steel 304 Working environment Indoor Dimension 1200x280x990 ,mm Arm Length : 500mm Warranty 1 Year
<b>CMC303</b> (>3pcs)	<b>34,000.00</b>		<b>ระบบประตูโรงงาน Turnstile รุ่น CMC303</b> Power AC220V+-10V, 50Hz/AC110+-10V,60Hz Passage Width : <=500mm Power Consumption : 30W Communication Interface RS485 (Distance : <=1200) Material : Housing - 304 stainless steel arm - stainless steel Environment : Indoors or outdoors with shed	<b>ระบบประตูโรงงาน Turnstile รุ่น CMC303</b> Power Supply 220VAC 50Hz Temperature -15°C to +60°C Humidity<math>\leq 90\%</math> Working Voltage of motor 24VDC Max Power consumption 30 W Passage Width $\leq$ 500mm Passing Speed 35 people/min (Access Control) Control interface Relay signal input Material Stainless Steel 304 Working environment Indoor Dimension 1200 x 330 x 990 mm Warranty 1 Year
<b>CMC305</b> (>3pcs)	<b>47,600.00</b>		<b>ระบบประตูโรงงาน Turnstile รุ่น CMC305</b> Power AC220V+-10V, 50Hz/AC110+-10V,60Hz Two way card reader (option reader) Passage Width : <=500mm Communication Interface RS485 (Distance : <=1200) Material : Housing - 304 stainless steel arm - stainless steel Environment : Indoors or outdoors with shed	<b>ระบบประตูโรงงาน Turnstile รุ่น CMC305</b> Power Supply 220VAC 50Hz Temperature -15°C to +60°C Humidity<math>\leq 90\%</math> Working Voltage of motor 24VDC Max Power consumption 30 W Passage Width $\leq$ 500mm Passing Speed 40 people/min (Access Control) Control interface Relay signal input Material Stainless Steel 304 Working environment Indoor Dimension 1200*280*990 mm Warranty 1 Year
<b>CMC402</b> (>2pcs)	<b>44,200.00</b>		<b>เครื่องกั้นทางเดิน Swing Gate รุ่น CMC402</b> Power Supply 220VAC Max Power consumption 30 W Passage Width $\leq$ 600 mm Passing Speed 35 person/min (Card Access Control) Working Environment Indoor	<b>เครื่องกั้นทางเดิน Swing Gate รุ่น CMC402</b> Power Supply 220VAC Max Power consumption 30 W Passage Width $\leq$ 600 mm Passing Speed 35 person/min (Card Access Control) Gate Opening and Closing Time 0.5-2 Seconds Control Interface Relay Signal Input Box Material Stainless Steel 304 Swing Arm Material Stainless Steel 304 Working Environment Indoor Dimension 380*280*990 mm Warranty 1 Year
<b>CMD606</b> (>2pcs)	<b>51,400.00</b>		<b>ระบบประตูโรงงาน Turnstile and Swing Gate รุ่น CMD606</b> Size : 1200*280*980mm Unlock time : 0.2s Pass rate : 35 person/min Power consumption : 35w Price for 1 Side	<b>ระบบประตูโรงงาน Turnstile and Swing Gate รุ่น CMD606</b> Size : 1200*280*980mm Unlock time : 0.2s Pass rate : 35 person/min Power consumption : 35w Price for 1 Side Warranty 1 Year
<b>CMD606-2</b> (>1pcs)	<b>71,100.00</b>		<b>ระบบประตูโรงงาน Turnstile and Swing Gate รุ่น CMD606-2</b> เพิ่มตัวกลาง Size : 1200*280*980mm Unlock time : 0.2s Pass rate : 35 person/min Power consumption : 35w	<b>ระบบประตูโรงงาน Turnstile and Swing Gate รุ่น CMD606-2</b> เพิ่มตัวกลาง Size : 1200*280*980mm Unlock time : 0.2s Pass rate : 35 person/min Power consumption : 35w Warranty 1 Year
<b>CMD701</b> (>2pcs)	<b>75,800.00</b>		<b>ระบบประตูโรงงาน Turnstile and Swing Gate รุ่น CMD701</b> Size : 1400*185*102mm Unlock time : 0.2s Pass rate : 35 person/min Power consumption : 35w Price for 1 Side	<b>ระบบประตูโรงงาน Turnstile and Swing Gate รุ่น CMD701</b> Size : 1400*185*102mm Unlock time : 0.2s Pass rate : 35 person/min Power consumption : 35w Price for 1 Side Warranty 1 Year



## FalCo Solution Access Control & Temperature Screening Terminal & Kiosk

FalCo Solution Co.,Ltd. 47/319, 5th floor, KaiTak Building, Popular Road, Ban Mai Subdistrict, Pak Kret District Nonthaburi Province, 11120 Thailand Tax ID: 0135558013787

Item No.	Price list (Baht) Exc.VAT	Picture	Main Function	Specifications
CMD701-2 (>1pcs)	118,500.00		ระบบประตูโรงงาน Turnstile and Swing Gate รุ่น CMD701 <b>เพิ่มเติมกลาง</b> Size : 1400*185*102mm Unlock time : 0.2s Pass rate : 35 person/min Power consumption : 35w	ระบบประตูโรงงาน Turnstile and Swing Gate รุ่น CMD701 <b>เพิ่มเติมกลาง</b> Size : 1400*185*102mm Unlock time : 0.2s Pass rate : 35 person/min Power consumption : 35w Warranty 1 Year
<b>LPR &amp; FalCo Cloud Management</b>				
LPRC300 (>4 PCS)	40,000.00		<b>LPRC300 Kit includes:</b> 1. License Plate Recognition Camera ZKTeco Logo; Thailand LPR algorithm; 2. LPR Camera Fixed Column Height:1.2-1.8m(Can be adjust) 3. LPR Camera Fill Light With photosensitive control 4. LPR Two-line LED Display Screen Warranty 1Year	LPRC300 Kit includes: 1. License Plate Recognition Camera ZKTeco Logo; กล้องอ่านป้ายทะเบียน ZKTeco จำนวน 1 ตัว 2. LPR Camera Fixed Column Height:1.2-1.8m(Can be adjust) แสงไฟส่องกล้องอ่านป้ายทะเบียน จำนวน 1 ตัว 3. LPR Camera Fill Light With photosensitive control ไฟ LED ชะแสงสว่างในเวลากลางคืน จำนวน 1 ตัว 4. LPR Two-line LED Display Screen ป้ายไฟ LED สองบรรทัดทะเบียนรถกล้องอ่านได้ แบบ 2 บรรทัด จำนวน 1 ตัว Warranty 1Year
LPR FCS Cloud	48,750.00		<b>FCS LPR Cloud Services Management by FalCo</b> - License Application - Integrate cloud service with API. - 50,000 Recognition / Month - Duration 1 Year after starting the cloud system - Warranty 1year	<b>FCS LPR Cloud Services Management by FalCo</b> - License Application - Integrate cloud service with API. - 50,000 Recognition / Month - Duration 1 Year after starting the cloud system - Warranty 1year
<b>Smart Kiosk Capacitive Touch</b>				
TK18.5	101,800.00		<b>18.5 inch Mini Kiosk</b> Warranty 1Year	18.5 inch Mini Kiosk Touch type: Capacitive Touch CPU: J1900 OS: Android / Window 10 is option RAM:4GB ROM:64GB SSD Interface: USB*4, RS232*2, RJ45*1 Wifi Pos Holder
TK23.8	117,900.00		<b>23.8 inch wall-mounted Kiosk</b> Warranty 1Year	23.8 inch wall-mounted Kiosk Touch type: Capacitive Touch CPU: J1900 OS: Android / Window 10 is option RAM:4GB ROM:64GB SSD Interface: USB*4, RS232*2, RJ45*1 Wifi Camera Thermal Printer 80mm Barcode / QR reader RFID Pos Holder
TK32.0	132,500.00		<b>32 inch wall-mounted Kiosk</b> Warranty 1Year	32 inch wall-mounted Kiosk Touch type: Capacitive Touch CPU: J1900 OS: Android / Window 10 is option RAM:4GB ROM:64GB SSD Interface: USB*4, RS232*2, RJ45*1 Power Supply: European standard Wifi Camera Thermal Printer 80mm Barcode / QR reader RFID Pos Holder
TKC23	177,600.00		<b>23 inch wall-mounted Kiosk + Cabinet</b> Warranty 1Year	23 inch wall-mounted Kiosk CPU: J1900 OS: Android / Window 10 is option RAM:4GB ROM:64GB SSD Interface: USB*4, RS232*2, RJ45*1 Wifi Thermal Printer 80mm Barcode / QR reader RFID Pos Holder
TKC27	201,800.00		<b>27 inch wall-mounted Kiosk + Cabinet</b> Warranty 1Year	27 inch wall-mounted Kiosk CPU: J1900 OS: Android / Window 10 is option RAM:4GB ROM:64GB SSD Interface: USB*4, RS232*2, RJ45*1 Wifi Thermal Printer 80mm Barcode / QR reader RFID Pos Holder

## FalCo Solution Access Control & Temperature Screening Terminal & Kiosk

FalCo Solution Co.,Ltd. 47/319, 5th floor, KaiTak Building, Popular Road, Ban Mai Subdistrict, Pak Kret District Nonthaburi Province, 11120 Thailand Tax ID: 0135558013787

Item No.	Price list (Baht) Exc.VAT	Picture	Main Function	Specifications
TKC32	238,300.00		<b>32 inch wall-mounted Kiosk + Cabinet</b> Warranty 1Year	32 inch wall-mounted Kiosk CPU: J1900 OS: Android / Window 10 is option RAM:4GB ROM:64GB SSD Interface: USB*4, RS232*2, RJ45*1 Wifi Thermal Printer 80mm Barcode / QR reader RFID Pos Holder
TKCS27 TKCS32	Please Call		<b>27 - 32 inch standing-type Kiosk + Cabinet</b> This picture is just for reference, will make new design according all function details. Warranty 1Year	27 - 32 inch standing-type Kiosk Touch type: Capacitive Touch CPU: i5 4th OS: Android / Window 10 is option RAM:4GB ROM: 64GB SSD Interface: USB*4, RS232*2, RJ45*1 Wifi <span style="color: red;">Option Please Call for Quotation</span> <span style="color: red;">Camera for Face Register</span> <span style="color: red;">Thermal Printer</span> <span style="color: red;">Barcode / QR reader</span> <span style="color: red;">RFID card Reader</span> <span style="color: red;">Passport scanner</span> <span style="color: red;">Cash acceptor NV9</span> <span style="color: red;">Coin returner ( single denomination)</span> <span style="color: red;">POS holder</span>